

This information was generated by the HP KEYMARK database on 13 Feb 2023

[Login](#)

Summary of	Hi -Therma Integra 8kW	Reg. No.	011-1W0580
Certificate Holder			
Name	Qingdao Hisense Hitachi Air-conditioning Systems Co.,Ltd.		
Address	Qianwangang Road	Zip	266555
City	Qingdao, Shandong	Country	China
Certification Body	DIN CERTCO Gesellschaft für Konformitätsbewertung mbH		
Subtype title	Hi -Therma Integra 8kW		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R32		
Mass of Refrigerant	1.05 kg		
Certification Date	10.02.2023		
Testing basis	HP KEYMARK certification scheme rules rev. 11		

Model: AHW-080HCDS1/AHS-080HCDSAA-23

Configure model	
Model name	AHW-080HCDS1/AHS-080HCDSAA-23
Application	Heating + DHW + low temp
Units	Indoor + Outdoor
Climate Zone	n/a
Reversibility	Yes
Cooling mode application (optional)	n/a

General Data	
Power supply	1x230V 50Hz

Heating

EN 14511-2		
	Low temperature	Medium temperature
Heat output	8.02 kW	8.02 kW
El input	1.58 kW	2.78 kW
COP	5.07	2.88

EN 14511-3 at 15 °C / 60 °C (Annex A Part D)		
	Low temperature	Medium temperature
Heat output	8.02 kW	8.02 kW
El input	1.58 kW	2.78 kW
COP	5.07	2.88

This information was generated by the HP KEYMARK database on 13 Feb 2023

EN 14511-4	
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

Average Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	42 dB(A)	42 dB(A)
Sound power level outdoor	64 dB(A)	64 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	198 %	135 %
Prated	6.55 kW	6.25 kW
SCOP	5.03	3.44
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	5.79 kW	5.53 kW
COP Tj = -7°C	3.10	1.96

This information was generated by the HP KEYMARK database on 13 Feb 2023

Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = +2°C	3.59 kW	3.26 kW
COP Tj = +2°C	4.87	3.42
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = +7°C	2.48 kW	2.19 kW
COP Tj = +7°C	6.74	4.56
Cdh Tj = +7 °C	0.900	0.900
Pdh Tj = 12°C	2.06 kW	2.18 kW
COP Tj = 12°C	10.86	7.86
Cdh Tj = +12 °C	0.900	0.900
Pdh Tj = Tbiv	5.79 kW	5.53 kW
COP Tj = Tbiv	3.10	1.96
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	6.23 kW	5.72 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	2.69	1.54
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	60 °C	60 °C
Poff	10 W	10 W
PTO	11 W	11 W
PSB	11 W	11 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.30 kW	0.50 kW

This information was generated by the HP KEYMARK database on 13 Feb 2023

Annual energy consumption Q_{he}	2690 kWh	3754 kWh
------------------------------------	----------	----------

Domestic Hot Water (DHW)

Average Climate

EN 16147	
Declared load profile	XL
Efficiency η_{DHW}	135 %
COP	3.30
Heating up time	2:4 h:min
Standby power input	28.0 W
Reference hot water temperature	46.0 °C
Mixed water at 40°C	230 l